



## Safety Data Sheet

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System  
Date of Revision: 12/11/2020 Revision: 04

### Section 1 - Chemical Product and Company Identification

1.1 Product Name: **Fuel System Cleaner**

1.2 Synonym: Blend

1.3 VP Racing Fuels, Inc., 7124 Richter Road, Elmhurst, TX 78112, 210.635.7744

1.4 Recommended Use: Fuel system treatment

1.5 **RESTRICTIONS on USE** THIS FUEL INJECTION CLEANER IS FOR GASOLINE ENGINES ONLY.

1.6 Emergency Response Number: **CHEMTREC 800-424-9300**  
International Emergency Telephone Number: 703-527-3887

1.7 See Section 16.3 for CHEMTREC in Country Emergency Numbers.

### Section 2 - Hazards Identification

#### 2.1 GHS HAZARD

##### Hazard Classes

##### Hazard Categories

Flammable liquid/vapor

Category 3

Aspiration Hazard

Category 1

Eye Irritation

Category 2A

Skin Irritation

Category 2

Specific Target Organs toxicity single exposure

Category 3

Specific Target Organs toxicity repeat exposure

Category 1&2

Acute Toxicity (Oral)

Category 4

Acute Toxicity (Inhalation)

Category 4

Acute Toxicity (Dermal)

Category 4

Mutagenicity

Category 1B

Carcinogenicity

Category 1B

Toxic to aquatic life with long-lasting effects

Category 2

2.2 Signal Word: **Danger**

# Fuel System Cleaner

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System



Flame

Irritant

Health

Aquatic Hazard

## 2.3 Pictograms:

## 2.4 Hazard Statements

### PHYSICAL HAZARDS:

H226: Flammable liquid and vapor.

### HEALTH HAZARDS:

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enter airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects.

H350: May cause cancer.

H372: Causes damage to organs through prolonged or repeated exposure.

### ENVIRONMENTAL HAZARDS:

H411: Toxic to aquatic life with long-lasting effects.

### PRECAUTIONARY STATEMENTS:

P102: Keep out of reach of children.

P201: Obtain special instructions before use  
**READ SDS BEFORE USE.**

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from sparks and open flames-  
No smoking.

P223: Keep container tightly closed

P240: Ground or bond container and receiving equipment.

P241: Use explosion-proof equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260: Do not breathe mist.

P264: Wash hands thoroughly after handling

P270: Do not eat, drink, or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

# Fuel System Cleaner

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

P280: Wear protective gloves, clothing, and eye protection.

## RESPONSE STATEMENTS:

P301 +P310+ P331: IF SWALLOWED: the USA Immediately call the National POISON CENTER at **800-222-1222**. OUTSIDE USA Immediately call a poison center or doctor. DO NOT induce vomiting.

P303+P361+353: IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340: IF INHALED: Remove to fresh air and keep comfortable for breathing.

P305+P351: IF IN EYES: Rinse cautiously with water for at least 15 minutes.

P308+P313: If exposed or concerned, get medical attention.

P313+P332+P337: If skin or eye irritation persists, get medical attention.

H314: Get medical attention if you feel unwell.

P330: Rinse mouth.

P362+P364: IF ON CLOTHING, take off contaminated clothing and wash it before reuse.

P370: In case of fire, use foam, carbon dioxide, dry chemicals to extinguish the fire.

P391 Collect spillage.

## STORAGE STATEMENTS:

P403+P235: Store in a well-ventilated place.

Keep cool.

P405: Store locked up.

## DISPOSAL STATEMENTS:

P501: Dispose of content and container following local, regional, national, or international regulations.

2.5 Hazards not otherwise classified (HNOC) or not covered by GHS: Repeated exposure may cause skin dryness or cracking.

## Section 3 - Composition / Information on Ingredients

### 3.1

CAS#	EC#	Chemical Names	Percent	Classification
N/A	N/A	Blend of Hydrocarbons, polymers, and modified glycol ether	100%	None

# Fuel System Cleaner

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

## 3.2 Blend Contains

Chemical Names	CAS#	EC#	Classification
3-Oxa-1-heptanol	111-76-2	203-905-0	Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Irrit. 2 H315, Eye Irrit 2, H319, Acute Tox. 4 H332
Naphtha (petroleum), light alkylate	64741-66-8	265-068-8	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit 2, H319, STOT SE 3 Central nervous Sys Inhalation H336, Muta. 1B H340, Carc. 1B H350, Aquatic Chronic 2 H411
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	265-185-4	Asp. Tox. 1 H304, Muta 1B H340, Carc 1B H350, STOT RE1 H372
Oxirane, 2-ethyl-, homopolymer, 2-aminoethyl ethyl tridecyl ether, branched	959934-87-3	None listed	Not Classified

**3.3 Trade Secret Provision and Chemical Concentration Disclosure:** Per OSHA and GHS Regulations, we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a blend and apply to the hazards identified in this Safety Data Sheet.

## Section 4 - First Aid Measures

**4.1 Eye:** Contact with the eyes can cause severe irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

**Eyes:** Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

**4.2 Skin:** Prolonged and repeated liquid contact can cause defatting and drying of the skin and lead to irritation and dermatitis.

**Skin:** Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

**4.3 Ingestion:** Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonia, pulmonary edema, and even death.

**Ingestion:** Do NOT induce vomiting. Get medical aid immediately.

**4.4 Inhalation:** Prolonged breathing of high vapor concentrations can produce headache, dizziness, nausea, and impaired vision. Extreme overexposure can cause central nervous system depression, loss of consciousness, liver damage, and death resulting from respiratory failure.

**Inhalation:** Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

# Fuel System Cleaner

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

**4.5 After first aid, get appropriate paramedic or community medical support.** The severity of the outcome following exposure may be related to the time between the exposure and treatment, rather than the amount of the exposure. Therefore, there is a need for rapid treatment of any exposure.

**4.6 Note to Physicians:** If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment, we will immediately disclose the specific chemical identity. Call CHEMTREC at 800-424-9300 or 703-527-3887. We will require a written statement of need and confidentiality agreement, per OSHA's Trade Secret Regulations, as soon as circumstances permit. In non-emergency situations, we will, upon written request, disclose a specific chemical identity.

## Section 5 - Fire-Fighting Measures

**5.1 General Fire Hazards:** Use water to cool containers exposed to fire.

**5.2 Hazardous Combustion Products:** Avoid fumes of burning products.

**5.3 Extinguishing Media:** Carbon dioxide, dry chemical, foam.

**5.4 Fire Fighting Equipment/Instructions:** Firefighters should wear full-face, self-contained breathing apparatus, and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

## Section 6 - Accidental Release Measures

**6.1 Spill /Leak Procedures:** Ventilate area. Wear adequate protective equipment. Spillages of the liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.

**6.2 Spills:** Avoid direct contact with the material. Stop leak if without risk. Move containers from the spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite, or diatomaceous earth and place it in a container for disposal.

## Section 7 - Handling and Storage

**7.1 Handling Precautions:** Keep away from ignition sources such as heat, sparks, and open flames. NO SMOKING Take precautionary measures against static discharge. Non-sparking tools should be used. Wear protective gloves, clothing, and eye protection. Wash thoroughly after handling. Use good personal hygiene practices and wear appropriate personal protective equipment. Empty containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other ignition sources. They may explode and cause injury or death.

**7.2 Storage Requirements:** Store in original manufacture container tightly closed container in a cool, dry, and well-ventilated area.

**7.3 Chemical Incompatibilities:** Strong oxidizing agents and strong reducing agents.

## Section 8 - Exposure Controls / Personal Protection

### 8.1

Chemical Names	ACGIH- TLV	OSHA - PEL
Blend of Hydrocarbons, polymers, and modified glycol ether	25 ppm	50 ppm



# Fuel System Cleaner

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

## 8.2

**ACGIH®** = American Conference of Governmental Industrial Hygienists. **TLV®** = Threshold Limit Value. **OSHA** = US Occupational Safety and Health Administration. **PEL** = Permissible Exposure Limits.

**NOTE: TWA Means** "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour workweek which shall not be exceeded."

**8.3 Ventilation:** Provide a general or local exhaust ventilation system to maintain airborne concentrations below TLV/PELs. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

**8.4 Contaminated Equipment:** Separate contaminated work clothes from street clothes and launder before reuse.

Remove this material from your shoes and clean personal protective equipment.

## 8.5 Personal protective equipment

Respiratory protection

Where risk assessment shows that air-purifying respirators are appropriate for a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) cartridges as a backup to engineering controls, if the respirator is the sole means of protection, use a full-face supplied-air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Registered trademark of The Chemours Company FC, LLC.

Eye protection

Face shield and safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Impervious clothing, flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace

## 8.6 Protective Clothing Pictograms



Splash Goggles



Gloves



Protective Apron



Vapor Respirator

# Fuel System Cleaner

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

## Section 9 - Physical and Chemical Properties

### 9.1

**Physical State:** Liquid

**Appearance:** Orange

**Odor:** Hydrocarbon solvent order

**Vapor Pressure:** Not Available

**Vapor Density (Air=1):** >1

**Specific Gravity (H<sub>2</sub>O=1,):** 0.75

**Relative Density:** Not Available

**Odor Threshold:** Not Available

**Flammability (solid, gas):** Not applicable.

**Evaporation rate:** Not Available

**Partition coefficient octanol/water:** Not Available

**pH:** None

**Water Solubility:** Insoluble in water

**Flash Point:** 138.2°F (59°C) closed cup

**Boiling Point/Range:** 275-410°F (135-210°C)

**Lower Explosive Limits (vol % in air):** 1%

**Upper Explosive Limits (vol % in air):** 10%

**Melting Point:** Not Available

**Viscosity:** <20.5mm<sup>2</sup>/s104°F,40°C

**Autoignition Temperature:** Not Available

**Decomposition temperature:** Not Available

## Section 10 - Stability and Reactivity

**10.1 Stability:** Stable under ordinary conditions of use and storage.

**10.2 Polymerization:** Hazardous polymerization has not been reported.

**10.3 Chemical Incompatibilities:** Strong oxidizing agents and Perchloric Acid

**10.4 Hazardous Decomposition Products:** Peroxides

**10.5 Conditions to Avoid:** Temperatures above 62°C, heat, sparks, open flames, other ignition sources.

Attacks some stainless steels, Light metals giving off hydrogen. Attacks some plastics, like chlorinated polyvinyl chloride (CPVC), polyvinyl chloride (PVC), polyethylene terephthalate, high-density polyethylene, and ethylene vinyl acetate; elastomers, like Viton (FKM), nitrile Buna-N (NBR), chloroprene, isoprene, natural rubber, polymethacrylate (acrylic) and silicone; and coatings, such as coal tar epoxy, epoxy general purpose and epoxy chemical resistant.

## Section 11- Toxicological Information

### 11.1

Acute Toxicity Estimate for this blend (ATE)

ATE (Oral): 1219 mg/kg

ATE (Dermal): 1086 mg/kg

ATE (Inhalation vapor/mist): 4.4 mg/l mist

**11.1.1** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause Harmful Oral Toxicity.

**11.1.2** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause Toxic Dermal Toxicity.

**11.1.3** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause Harmful Inhalation Toxicity.

# Fuel System Cleaner

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

**11.2 Route of Entry:** Inhalation, Ingestion, Absorption, Skin, and Eye Contact.

**11.3 Aspiration Hazard:** European Chemical Agency Database shows that this product's components may be fatal if swallowed and enters airways.

**11.4 Mutagenicity:** OECD Guideline Test results found in the European Chemical Agency Database show this product's components to cause genetic defects.

**11.5 Skin Corrosion/Irritation:** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause skin irritation. Repeated exposure may cause skin dryness or cracking.

**11.6 Serious Eye Damage/Irritation:** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause serious eye irritation.

**11.7 Reproductive toxicity:** OECD Guideline Test results found in the European Chemical Agency Database show no components of this product to cause damage fertility or the unborn child.

**11.8 Skin Sensitization** OECD Guideline Tests results found in the European Chemical Agency Database show no product components to cause skin sensitivity.

**11.9 Respiratory Sensitization** OECD Guideline Tests results found in the European Chemical Agency Database show no product components to cause respiratory sensitivity.

**11.10 Specific Target Organ Toxicity (Single Exposure):** European Chemical Agency Database shows that no components of this product may cause damage organs due to a single exposure. However, human exposure above 200 ppm can be expected to cause narcosis, damage to the kidney and liver, and present an abnormal blood picture showing erythropenia, reticulocytosis, granulocytosis, leukocytosis. It would be likely to cause fragility of erythrocytes and hematuria.

**11.11 Specific Target Organ Toxicity (Repeated Exposure):** European Chemical Agency Database shows that no product components may cause damage to organs due to repeat exposure. However, it may cause damage to the kidney and liver.

**11.12 Signs and Symptoms:** Effects due to exposure may include: Headache, Dizziness, Drowsiness, Metabolic Acidosis, Coma, Seizures. Swallowing results in a sour taste that turns to a burning sensation and is followed by numbness of the tongue, indicating paralysis of the sensory nerve endings. Central nervous system depression, headache, narcosis. Symptoms may be delayed

**11.13 Carcinogenicity:** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components can cause cancer.

Chemical Name	IARC	ACGIH	NTP	OSHA
Blend of Hydrocarbons, polymers, and modified glycol ether	Not classified as carcinogenicity to humans	A confirmed animal with unknown relevance to humans	Not listed	Not Listed



# Fuel System Cleaner

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

## Section 12 - Ecological Information

### 12.1

Product Name	Results	Species	Exposure
Blend of Hydrocarbons, polymers, and modified glycol ether	Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the environment		

**Toxicity:** OECD Guideline Test results found in the European Chemical Agency Database show this product's components to cause long-term toxicity to aquatic life.

**12.2 Mobility:** Floats on water

**12.3 Persistence/degradability:** Inconclusive technical data.

**12.4 Bioaccumulation:** Inconclusive technical data.

**12.5 Other adverse effects:** Inconclusive technical data.

## Section 13 - Disposal Considerations

**13.1 Disposal: DO NOT REUSE EMPTY CONTAINER!** The container should be completely emptied before discard. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

## Section 14 - Transport Information

### 14.1 DOT Transport Information



**ID No.:** UN 3295

**Shipping Name:** Hydrocarbons, liquid, n.o.s.

**Hazard Class:** 3

**Packing Group:** III

**Label:** Flammable

**Placard:** Flammable

**Marking:** MARINE POLLUTANT Naphtha (petroleum), light alkylate when shipping ground greater than 119 gallons single container or any quantity by water

# Fuel System Cleaner

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

## 14.2 IMDG Transport Information



**ID No.:** UN 3295

**Shipping Name:** HYDROCARBONS, LIQUID, N.O.S.

**Hazard Class:** 3

**Packing Group:** III

**Flash Point:** (59 °C c.c.)

**EmS Number:** F-E, S-E

**Label:** Flammable

**Placard:** Flammable

**Marking:** Marine Pollutant Naphtha (petroleum), light alkylate

## 14.3 UN Dangerous Goods Transport Information



**ID No.:** UN 3295

**Shipping Name:** Hydrocarbons, liquid, n.o.s.

**Hazard Class:** 3


**Packing Group:** III

**Label:** Flammable

**Placard:** Flammable

**Marking:** Marine Pollutant Naphtha (petroleum), light alkylate

## 14.4



Use marking when shipping as a limited quantity ground in the US

## DOT Transport Limited Quantity/Consumer Commodity

Inner packaging not over


5.0L (1.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each

# Fuel System Cleaner

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

14.5



Use marking when shipping as a limited quantity by vessel.

## IMDG Transport Limited Quantity

Inner packaging not over

5.0L (1.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each

**ID No.:** UN 3295

**Shipping Name:** HYDROCARBONS, LIQUID, N.O.S. LTD.QTY.

**Hazard Class:** 3

**Packing Group:** III

**Flash Point:** (59° C c.c.)

**EmS Number:** F-E, S-E

## Section 15 - Regulatory Information

### 15.1 US Regulations:

**TSCA:** All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

**Toxic Release Inventory (TRI):** This product doesn't contain any chemicals listed in EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know- Act of 1986 (40 CFR 372).

**CERCLA Hazardous Substances and corresponding RQs:** None

**SARA Community Right-to-Know Program:** All components of this blend.

**Clean Water Act:** None

**Clean Air Act:** None

**OSHA:** All ingredients are listed in 1910.1200.

### State Regulations

**California prop. 65:** None

### Chemicals on the following State Right to Know Lists:

**Massachusetts:** All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements.

**New Jersey:** All components of this product are on the New Jersey inventory or are exempt from Inventory requirements.

**Pennsylvania:** All components of this product are on the Pennsylvania Inventory or are exempt from Inventory requirements.

# Fuel System Cleaner

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

## 15.2

### International Regulations:

**Australian Inventory of Chemical Substances:** All components of this product are on the Inventory or are exempt from Inventory requirements.

**National Existing Chemical Inventory in Taiwan:** All components of this product are on Inventory or are exempt from Inventory requirements.

**Philippine Inventory of Chemicals and Chemical Substances** All components of this product are on the Inventory or are exempt from Inventory requirements.

**China Existing Chemical Inventory:** All components of this product are on the Inventory or are exempt from Inventory requirements.

## Section 16 - Other Information

**16.1 Disclaimer:** The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall determine the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

**16.2 References:** CHEMpendium Database of Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller online, European Chemical Agency Database, and MSDS and SDS of chemicals in this mixture.

### 16.3 CHEMTREC in-country emergency dial numbers:

County	Greeting Language	City	Local number	Toll-Free number
Argentina	Latin American Spanish	Buenos Aires	54-1159839431	
Brazil	Portuguese	Rio De Janeiro	55-2139581449	
Brazil	Portuguese	Sao Paulo	55-1143491359	
Brazil - Toll-Free	Portuguese		0800 892 0479	0800 892 0479
Cayman Islands	English	Local (National)	345-749-8392	
Chile	Latin American Spanish	Santiago	56 2 2581 4934	
Colombia	Latin American Spanish		01800-710-2151	01800-710-2151
Costa Rica	Latin American Spanish		506-40003869	
Dominican Republic	Latin American Spanish	Santo Domingo	1 (829) 956-7588	
El Salvador	Latin American Spanish	San Salvador	503 2136 7633	
Grenada	English	St George	1 (473) 230-0165	
Guinea	French		224 660 71 03 00	
Mexico	Latin American Spanish		01-800-681-9531	01-800-681-9531

# Fuel System Cleaner

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

Panama	Latin American Spanish		507-8322475	
Peru	Latin American Spanish	Lima	51-17071295	
Trinidad and Tobago	English	National Number	1-868-224-5716	

County	Greeting Language	City	Local number	Toll-Free number
India	Hindi, Bengali, English		000-800-100-7141	000-800-100-7141
Indonesia	Indonesian		001-803-017-9114	001-803-017-9114
Israel	Hebrew	Tel Aviv	972-37630639	
Japan	Japanese	Tokyo	81-345209637	
Malaysia	Malay	Kuala Lumpur	60-392125794	1-800-815-308
Philippines	Tagalog	Manila	+63 2 8395 3308 and 1-800-1-116-1020	1-800-1-116-1020
Russia	Russian		8-800-100-6346	8-800-100-6346
Saudi Arabia	Arabic and English		966-8111095861	
Singapore	English and Mandarin		65-31581349	800-101-2201
South Korea	Korean			003-0813-2549 and 080-822-1374
Taiwan	Mandarin	Taipei	886-2-7741-4207	00801-14-8954
Thailand	Thai		001-800-13-203-9987	001-800-13-203-9987
India	Hindi, Bengali, English		000-800-100-7141	000-800-100-7141

County	Greeting Language	City	Local number	Toll-Free number
Australia	English	Sydney	61-290372994	
New Zealand	English	Auckland	64-98010034	

County	Greeting Language	City	Local number	Toll-Free number
South Africa	English	None	0-800—983-611	0-800—983-611

**16.4 SDS Preparation Date** 01/27/2016

**SDS Previous Issue Date:** None

**SDS Revision Date:** 07/18/2017 Sections 2,4,5 9,11 14

**SDS Revision Date:** 12/26/2017 Sections 2,3,8,11

**SDS Revision Date:** 08/05/2019 Sections 2,3,8,11,13,14,15,16

**SDS Revision Date:** 12/11/2020 Sections 1,2,11,16

Prepared by SJC Compliance Education, Inc.

1319 Varese Dr.

Pearland, TX 77581

[steve@sjcedu.org](mailto:steve@sjcedu.org)