



# SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10

Revision Date: 10/05/2020

Print Date:  
10/11/2020

29 CFR 1910.1200 (OSHA HazCom 2012)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : Valvoline™ VR1™ SAE 20W-50  
Motor Oil

Product code : 822347

### Details of the supplier of the safety data sheet

Valvoline LLC  
100 Valvoline Way  
Lexington, KY 40509  
United States of America (USA)  
1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

### Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

### Regulatory Information Number

1-800-TEAMVAL (1-800-832-6825)

### Product Information

1-800-TEAMVAL (1-800-832-6825)

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Eye irritation : Category 2A

### GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : Causes serious eye irritation.

Precautionary Statements : **Prevention:**

Wear eye protection/ face protection.  
Wash skin thoroughly after handling.

### **Response:**

If eye irritation persists: Get medical advice/ attention.  
IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.



## SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10

Revision Date: 10/05/2020

Print Date:  
10/11/2020

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

### Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	Not a hazardous substance or mixture.	$\geq 70.00$ - $< 80.00$
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	Not a hazardous substance or mixture.	$\geq 1.50$ - $< 5.00$
Zinc O,O,O',O'-tetrakis(1,3- dimethylbutyl) bis(phosphorodithioate)	2215-35-2	Skin Irrit. 2; H315  Eye Dam. 1; H318	$\geq 1.50$ - $< 5.00$

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

- General advice : Do not leave the victim unattended.  
Show this safety data sheet to the doctor in attendance.  
Move out of dangerous area.
- If inhaled : If breathed in, move person into fresh air.  
If unconscious, place in recovery position and seek medical  
advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash contaminated clothing before re-use.  
If on skin, rinse well with water.  
Remove contaminated clothing. If irritation develops, get  
medical attention.
- In case of eye contact : Protect unharmed eye.  
Remove contact lenses.  
Immediately flush eye(s) with plenty of water.
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.



## SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10

Revision Date: 10/05/2020

Print Date:  
10/11/2020

If symptoms persist, call a physician.

Most important symptoms  
and effects, both acute and  
delayed

: No symptoms known or expected.  
Causes serious eye irritation.

Notes to physician

: No hazards which require special first aid measures.

---

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media

: Use extinguishing measures that are appropriate to local  
circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing  
media

: High volume water jet

Specific hazards during  
firefighting

: Do not allow run-off from fire fighting to enter drains or water  
courses.

Hazardous combustion  
products

: carbon dioxide and carbon monoxide

Specific extinguishing  
methods

:

Product is compatible with standard fire-fighting agents.

Further information

: Standard procedure for chemical fires.

Special protective equipment  
for firefighters

: In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,  
protective equipment and  
emergency procedures

: Persons not wearing protective equipment should be excluded  
from area of spill until clean-up has been completed.  
Use personal protective equipment.

Environmental precautions

: Prevent further leakage or spillage if safe to do so.

Methods and materials for  
containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,  
acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.



## SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10

Revision Date: 10/05/2020

Print Date:  
10/11/2020

Other information : Comply with all applicable federal, state, and local regulations.

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Dispose of rinse water in accordance with local and national regulations.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Avoid contact with skin and eyes.  
Container hazardous when empty.  
Do not smoke.  
Do not breathe vapours/dust.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable particulate matter	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable particulate matter	ACGIH



## SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10

Revision Date: 10/05/2020

Print Date:  
10/11/2020

		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

### Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

### Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear resistant gloves (consult your safety equipment supplier).  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Safety shoes  
Impervious clothing  
Wear as appropriate:

Hygiene measures : When using do not smoke.  
When using do not eat or drink.  
Wash hands before breaks and at the end of workday.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : amber

Odour : mild

Odour Threshold : No data available



## SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10

Revision Date: 10/05/2020

Print Date:  
10/11/2020

---

pH	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	600.01 °F / 315.56 °C (1,013.333333 hPa) Calculated Phase Transition Liquid/Gas
Flash point	:	394 - 480 °F / 201 - 249 °C  Method: closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	7 %(V) GLP: Calculated Explosive Limit
Lower explosion limit / Lower flammability limit	:	0.9 %(V) GLP: Calculated Explosive Limit
Vapour pressure	:	0.1 hPa (68 °F / 20 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	0.8880 (60.01 °F / 15.56 °C)
Density	:	0.8816 g/cm3 (60.01 °F / 15.56 °C)
Solubility(ies)		
Water solubility	:	negligible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	182 mm2/s (104 °F / 40 °C)
Oxidizing properties	:	No data available



## SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10

Revision Date: 10/05/2020

Print Date:  
10/11/2020

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: None known.
Incompatible materials	: Strong oxidizing agents Acids
Hazardous decomposition products	No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Eye Contact  
Ingestion

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method

#### Components:

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity	: LD50 (Rat): > 15 g/kg
Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity	: LD50 (Rat): > 15 g/kg
Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg

#### **Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate):**

Acute oral toxicity	: LD50 (Rat): 2,230 mg/kg
---------------------	---------------------------



## SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10

Revision Date: 10/05/2020

Print Date:  
10/11/2020

GLP: no

Acute inhalation toxicity : LC50 (Rat): > 2.3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: Not classified as acutely toxic by inhalation under GHS.  
Remarks: Information given is based on data obtained from similar substances.

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg  
Method: OECD Test Guideline 402  
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

### Skin corrosion/irritation

Not classified based on available information.

#### Product:

Remarks : May cause skin irritation in susceptible persons.

#### Components:

##### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

##### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

##### **Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate):**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Irritating to skin.  
GLP : yes

### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Product:

Remarks : Causes serious eye irritation.  
Vapours may cause irritation to the eyes, respiratory system and the skin.

#### Components:

##### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation  
Assessment : No eye irritation

##### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation  
Assessment : No eye irritation





## SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10

Revision Date: 10/05/2020

Print Date:  
10/11/2020

### **Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:**

Result : Corrosive

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Components:**

### **Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:**

Species : Guinea pig  
Assessment : Did not cause sensitisation on laboratory animals.  
Method : OECD Test Guideline 406  
Result : Did not cause sensitisation on laboratory animals.  
GLP : yes

### **Germ cell mutagenicity**

Not classified based on available information.

#### **Components:**

### **Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

#### **Components:**

### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

Not classified based on available information.



## SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10

Revision Date: 10/05/2020

Print Date:  
10/11/2020

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

### **Product:**

No aspiration toxicity classification

### **Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

No aspiration toxicity classification

### **Further information**

#### **Product:**

Remarks : No data available

---

## SECTION 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

#### **Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

### **Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l  
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment  
Short-term (acute) aquatic hazard : Not classified based on available information.



## SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10

Revision Date: 10/05/2020

Print Date:  
10/11/2020

Long-term (chronic) aquatic hazard : Not classified based on available information.

### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

#### Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

#### Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: OECD Test Guideline 203  
Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 23 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae : NOEL (Desmodesmus subspicatus (green algae)): 10 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 201  
Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.4 mg/l  
Exposure time: 21 d  
Test substance: WAF  
Method: OECD Test Guideline 211  
Remarks: Information given is based on data obtained from similar substances.

### Persistence and degradability

#### Components:

#### Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 1.5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B  
Remarks: Information given is based on data obtained from similar substances.



## SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10

Revision Date: 10/05/2020

Print Date:  
10/11/2020

No data available

### **Bioaccumulative potential**

#### **Components:**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n- : log Pow: Expected > 7  
octanol/water

No data available

### **Mobility in soil**

#### **Components:**

No data available

### **Other adverse effects**

No data available

#### **Product:**

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological  
information

: No data available

#### **Components:**

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

General advice

: Dispose of in accordance with all applicable local, state and federal regulations.

Send to a licensed waste management company.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Do not dispose of waste into sewer.

Contaminated packaging

: Do not re-use empty containers.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Dispose of as unused product.  
Empty remaining contents.

---

## SECTION 14. TRANSPORT INFORMATION

### **International Regulations**

#### **UNRTDG**

Not regulated as a dangerous good



## SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10

Revision Date: 10/05/2020

Print Date:  
10/11/2020

### IATA-DGR

Not regulated as a dangerous good

### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### 49 CFR

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Zinc O,O,O',O'- tetrakis(1,3- dimethylbutyl) bis(phosphorodit hioate	2215-35-2	>= 1 - < 5 %
--	-----------	--------------

Zinc, bis[O,O- bis(2-ethylhexyl) phosphorodithioa to-S,S']-, (T-4)-	4259-15-8	>= 0.1 - < 1 %
--	-----------	----------------



## SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10

Revision Date: 10/05/2020

Print Date:  
10/11/2020

### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

### Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

Zinc O,O,O',O'- tetrakis(1,3- dimethylbutyl) bis(phosphorodithioate	2215-35-2	>= 1 - < 5 %
--	-----------	--------------

This product does not contain any priority pollutants related to the U.S. Clean Water Act

### The components of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: On TSCA Inventory

### TSCA list

No substances are subject to TSCA 12(b) export notification requirements.

### Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)



## SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10


Revision Date: 10/05/2020

Print Date:  
10/11/2020

### SECTION 16. OTHER INFORMATION

#### Further information

Internal information : R0173128

NFPA:	HMIS III:						
<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard</p> 	<table><tr><td>HEALTH</td><td>2</td></tr><tr><td>FLAMMABILITY</td><td>1</td></tr><tr><td>PHYSICAL HAZARD</td><td>0</td></tr></table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

#### NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

#### Full text of H-Statements

H315 Causes skin irritation.  
H318 Causes serious eye damage.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction



## SAFETY DATA SHEET

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.10

Revision Date: 10/05/2020

Print Date:  
10/11/2020

FG : Food grade  
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
H-statement : Hazard Statement  
IATA : International Air Transport Association.  
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
IMDG : International Maritime Code for Dangerous Goods  
ISO : International Organization for Standardization  
logPow : octanol-water partition coefficient  
LCxx : Lethal Concentration, for xx percent of test population  
LDxx : Lethal Dose, for xx percent of test population.  
ICxx : Inhibitory Concentration for xx of a substance  
Ecxx : Effective Concentration of xx  
N.O.S.: Not Otherwise Specified  
OECD : Organization for Economic Co-operation and Development  
OEL : Occupational Exposure Limit  
P-Statement : Precautionary Statement  
PBT : Persistent , Bioaccumulative and Toxic  
PPE : Personal Protective Equipment  
STEL : Short-term exposure limit  
STOT : Specific Target Organ Toxicity  
TLV : Threshold Limit Value  
TWA : Time-weighted average  
vPvB : Very Persistent and Very Bioaccumulative  
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
DOT : Department of Transportation  
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
HMIRC : Hazardous Materials Information Review Commission  
HMIS : Hazardous Materials Identification System  
NFPA : National Fire Protection Association  
NIOSH : National Institute for Occupational Safety and Health  
OSHA : Occupational Safety and Health Administration  
PMRA : Health Canada Pest Management Regulatory Agency  
RTK : Right to Know  
WHMIS : Workplace Hazardous Materials Information System