



# SAFETY DATA SHEET

## Section 1. Identification

|                                                                                             |          |                                               |                         |                       |             |
|---------------------------------------------------------------------------------------------|----------|-----------------------------------------------|-------------------------|-----------------------|-------------|
| <b>Manufacturer</b>                                                                         |          | <b>Transportation Emergency (CHEMTREC)</b>    | <b>:</b>                | <b>1-800-424-9300</b> |             |
| <b>CHS Inc.</b>                                                                             |          |                                               |                         | <b>CCN23163</b>       |             |
| <b>P.O. Box 64089</b>                                                                       |          |                                               |                         |                       |             |
| <b>Mail station 525</b>                                                                     |          | <b>Technical Information</b>                  | <b>:</b>                | <b>1-651-355-8443</b> |             |
| <b>St. Paul, MN 55164-0089</b>                                                              |          | <b>SDS Information</b>                        | <b>:</b>                | <b>1-651-355-8445</b> |             |
| <b>Product name</b>                                                                         | <b>:</b> | Auto Gold Multi-Vehicle ATF Synthetic Blend   | <b>SDS no.</b>          | <b>:</b>              | 0202-071212 |
| <b>Common name</b>                                                                          | <b>:</b> | Synthetic Blend Automatic Transmission Fluid. | <b>Revision date</b>    | <b>:</b>              | 04/02/2020  |
| <b>Chemical name</b>                                                                        | <b>:</b> | Lubricating oil.                              | <b>Chemical formula</b> | <b>:</b>              | Mixture     |
| <b>Chemical family</b>                                                                      | <b>:</b> | Hydrocarbon.                                  |                         |                       |             |
| <b><u>Relevant identified uses of the substance or mixture and uses advised against</u></b> |          |                                               |                         |                       |             |
| Automatic transmission fluid.                                                               |          |                                               |                         |                       |             |

## Section 2. Hazards identification

|                                                |   |                                                                                                                                                                                                                                         |   |   |                                       |
|------------------------------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|---|---------------------------------------|
| OSHA/HCS status                                | : | This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).                                                                                                                                     |   |   |                                       |
| Classification of the substance or mixture     | : | SKIN SENSITIZATION - Category 1<br>ASPIRATION HAZARD - Category 1<br>AQUATIC HAZARD (ACUTE) - Category 3<br>AQUATIC HAZARD (LONG-TERM) - Category 3                                                                                     |   |   |                                       |
| <u>GHS label elements</u>                      |   |                                                                                                                                                                                                                                         |   |   |                                       |
| Hazard pictograms                              | : |                                                                                                                                                      |   |   |                                       |
| Signal word                                    | : | Danger                                                                                                                                                                                                                                  |   |   |                                       |
| Hazard statements                              | : | H317 - May cause an allergic skin reaction.<br>H304 - May be fatal if swallowed and enters airways.<br>H412 - Harmful to aquatic life with long lasting effects.                                                                        |   |   |                                       |
| <u>Precautionary statements</u>                |   |                                                                                                                                                                                                                                         |   |   |                                       |
| General                                        | : | Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.                                                                                                             |   |   |                                       |
| Prevention                                     | : | Wear protective gloves. Avoid release to the environment. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace.                                                                                   |   |   |                                       |
| Response                                       | : | IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. |   |   |                                       |
| Storage                                        | : | Store locked up.                                                                                                                                                                                                                        |   |   |                                       |
| Disposal                                       | : | Dispose of contents and container in accordance with all local, regional, national and international regulations.                                                                                                                       |   |   |                                       |
| Hazards not otherwise classified : None known. |   |                                                                                                                                                                                                                                         |   |   |                                       |
| Hazardous Material Information System (U.S.A.) |   | Health :                                                                                                                                                                                                                                | 3 | / | Flammability : 1 Physical hazards : 0 |
| National Fire Protection Association (U.S.A.)  |   | Health :                                                                                                                                                                                                                                | 3 |   | Flammability : 1 Instability : 0      |

### Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture  
**Chemical name** : Lubricating oil.  
**Other means of identification** : Synthetic Blend Automatic Transmission Fluid.

| Ingredient name                                        | %         | CAS number  |
|--------------------------------------------------------|-----------|-------------|
| Distillates (petroleum), hydrotreated light paraffinic | ≥50 - ≤75 | 64742-55-8  |
| Distillates (petroleum), hydrotreated heavy paraffinic | ≥25 - ≤50 | 64742-54-7  |
| Distillates (petroleum), hydrotreated light naphthenic | ≥1 - ≤3   | 64742-53-6  |
| Heterocyclic ether                                     | ≥1 - ≤3   | Proprietary |
| Alkyl acetamide                                        | ≥0.3 - ≤1 | Proprietary |
| Substituted hydrocarbyl sulfide                        | ≥0.3 - ≤1 | Proprietary |
| Long chain hydroxyalkylamine                           | ≥0.3 - <1 | Proprietary |

The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

**There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

**Eye contact** : If material comes in contact with the eyes, immediately wash the eyes with large amounts of water for 15 minutes, occasionally lifting the lower and upper lids. Get medical attention.  
**Inhalation** : If person breathes in large amounts of material, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the person warm and at rest. Get medical attention as soon as possible.  
**Skin contact** : If the material comes in contact with the skin, wash the contaminated skin with soap and water promptly. If the material penetrates through clothing, remove the clothing and wash the skin with soap and water promptly. If irritation persists after washing, get medical attention immediately.  
**Ingestion** : If material has been swallowed, do not induce vomiting. Get medical attention immediately.

#### Most important symptoms/effects, acute and delayed

##### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : May cause an allergic skin reaction.  
**Ingestion** : May be fatal if swallowed and enters airways.

##### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following: pain or irritation, watering, redness.  
**Inhalation** : Adverse symptoms may include the following: respiratory tract irritation, coughing.  
**Skin contact** : Adverse symptoms may include the following: irritation, redness.  
**Ingestion** : Adverse symptoms may include the following: nausea or vomiting

#### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.  
**Specific treatments** : No specific treatment.  
**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### Extinguishing media

**Suitable extinguishing media** : Use water spray to cool fire exposed surfaces and to protect personnel. Foam, dry chemical or water spray (fog) to extinguish fire.  
**Unsuitable extinguishing media** : None known.  
**Specific hazards arising from the chemical** : Toxic fumes gases or vapors may evolve on burning.  
**Hazardous thermal decomposition products** : No specific data.  
**Special protective actions for fire-fighters** : When fighting fires wear full turnout gear and self contained breathing apparatus. Water may cause splattering. Material floats on water.  
**Special protective equipment for fire-fighters** : Not applicable.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Keep unnecessary and unprotected personnel from entering. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

### Methods and materials for containment and cleaning up

- Spill** : Contain with dikes or absorbent to prevent migration to sewers/streams. Take up small spill with dry chemical absorbent; large spills may require pump or vacuum prior to absorbent. May require excavation of severely contaminated soil.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
- Conditions for safe storage, including any incompatibilities** : Do not store above the following temperature: 113°C (235.4°F). Odorous and toxic fumes may form from the decomposition of this product if stored at excessive temperatures for extended periods of time. Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### United States

#### Occupational exposure limits

| Ingredient name                                        | Exposure limits                                                                                                                                                                                                                                                                                                                              |
|--------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Distillates (petroleum), hydrotreated light paraffinic | <b>OSHA PEL (United States, 5/2018).</b><br>TWA: 5 mg/m <sup>3</sup> 8 hours.<br><b>ACGIH TLV (United States, 3/2018).</b><br>TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction<br><b>NIOSH REL (United States, 10/2016).</b><br>TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist<br>STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist |
| Distillates (petroleum), hydrotreated heavy paraffinic | <b>OSHA PEL (United States, 5/2018).</b><br>TWA: 5 mg/m <sup>3</sup> 8 hours.<br><b>ACGIH TLV (United States, 3/2018).</b><br>TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction<br><b>NIOSH REL (United States, 10/2016).</b><br>TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist<br>STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist |
| Distillates (petroleum), hydrotreated light naphthenic | <b>OSHA PEL (United States, 5/2018).</b><br>TWA: 5 mg/m <sup>3</sup> 8 hours.<br><b>ACGIH TLV (United States, 3/2018).</b><br>TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction<br><b>NIOSH REL (United States, 10/2016).</b><br>TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist<br>STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist |

- Appropriate engineering controls** : Use only with adequate ventilation.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

### Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Recommended: Splash goggles and a face shield, where splash hazard exists.
- Skin protection**
- Hand protection** : 4 - 8 hours (breakthrough time): Nitrile gloves.
- Body protection** : Recommended: Long sleeved coveralls.
- Other skin protection** : Recommended: Impervious boots.
- Respiratory protection** : If ventilation is inadequate, use a NIOSH-certified respirator with an organic vapor cartridge and P95 particulate filter.

## Section 9. Physical and chemical properties

|                                                     |                                 |                                               |                                                                   |
|-----------------------------------------------------|---------------------------------|-----------------------------------------------|-------------------------------------------------------------------|
| <b>Appearance</b>                                   |                                 | <b>Relative density</b>                       | : 0.85 to 0.86                                                    |
| <b>Physical state</b>                               | : Liquid.                       | <b>Evaporation rate</b>                       | : <1 (Butyl acetate = 1)                                          |
| <b>Color</b>                                        | : Red.                          | <b>Solubility</b>                             | : Insoluble in the following materials: cold water and hot water. |
| <b>Odor</b>                                         | : Mild.                         | <b>Solubility in water</b>                    | : Insoluble                                                       |
| <b>Odor threshold</b>                               | : Not available.                | <b>Partition coefficient: n-octanol/water</b> | : Not available.                                                  |
| <b>pH</b>                                           | : Not available.                | <b>Auto-ignition temperature</b>              | : >260°C (>500°F)                                                 |
| <b>Melting point</b>                                | : Not available.                | <b>Decomposition temperature</b>              | : Not available.                                                  |
| <b>Boiling point</b>                                | : Not available.                | <b>SADT</b>                                   | : Not available.                                                  |
| <b>Flash point</b>                                  | : Closed cup: >177°C (>350.6°F) | <b>Viscosity</b>                              | : Not available.                                                  |
| <b>Flammability</b>                                 | : Not available.                | <b>Vapor pressure</b>                         | : <0.13 kPa (<1 mm Hg) (68°F)                                     |
| <b>Lower and upper explosive (flammable) limits</b> | : Not available.                | <b>Vapor density</b>                          | : Not available.                                                  |

## Section 10. Stability and reactivity

|                                           |                                                                                                        |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------|
| <b>Reactivity</b>                         | : No specific test data related to reactivity available for this product or its ingredients.           |
| <b>Chemical stability</b>                 | : The product is stable.                                                                               |
| <b>Possibility of hazardous reactions</b> | : Under normal conditions of storage and use, hazardous reactions will not occur.                      |
| <b>Conditions to avoid</b>                | : No specific data.                                                                                    |
| <b>Incompatible materials</b>             | : Reactive or incompatible with the following materials: oxidizing materials.                          |
| <b>Hazardous decomposition products</b>   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name                                | Result    | Species | Dose        | Exposure |
|--------------------------------------------------------|-----------|---------|-------------|----------|
| Distillates (petroleum), hydrotreated light naphthenic | LD50 Oral | Rat     | >5000 mg/kg | -        |

#### Irritation/Corrosion

|                    |                                     |
|--------------------|-------------------------------------|
| <b>Skin</b>        | : Not hazardous (per manufacturer). |
| <b>Eyes</b>        | : Not hazardous (per manufacturer). |
| <b>Respiratory</b> | : Not hazardous (per manufacturer). |

#### Sensitization

| Product/ingredient name                                         | Route of exposure | Species          | Result                     |
|-----------------------------------------------------------------|-------------------|------------------|----------------------------|
| Substituted hydrocarbyl sulfide<br>Long chain hydroxyalkylamine | skin<br>skin      | Rabbit<br>Rabbit | Sensitizing<br>Sensitizing |

#### Mutagenicity

There is no data available.

#### Carcinogenicity

There is no data available.

#### Reproductive toxicity

There is no data available.

#### Teratogenicity

There is no data available.

#### Specific target organ toxicity (single exposure)

There is no data available.

**Specific target organ toxicity (repeated exposure)**

There is no data available.

**Aspiration hazard**

| Name                                                   | Result                         |
|--------------------------------------------------------|--------------------------------|
| Distillates (petroleum), hydrotreated light paraffinic | ASPIRATION HAZARD - Category 1 |

**Information on the likely routes of exposure** : Dermal contact. Eye contact. Inhalation. Ingestion.

**Section 12. Ecological information****Toxicity**

| Product/ingredient name | Result                        | Species            | Exposure          |
|-------------------------|-------------------------------|--------------------|-------------------|
| Heterocyclic ether      | EC50 23 mg/L<br>NOEC 0.4 mg/L | Daphnia<br>Daphnia | 2 days<br>21 days |

**Persistence and degradability**

There is no data available.

**Bioaccumulative potential**

There is no data available.

**Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>)** : There is no data available.

**Other adverse effects** : No known significant effects or critical hazards.

**Section 13. Disposal considerations**

**Disposal methods** : Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

**Section 14. Transport information**

**DOT IDENTIFICATION NUMBER** Not applicable. **DOT proper shipping name** Not applicable.

**DOT Hazard Class(es)** Not applicable. **PG** Not applicable. **DOT-TDG EMER. RESPONSE GUIDE NO.** Not applicable

**Section 15. Regulatory information**

**U.S. Federal regulations** : **TSCA 4(a) proposed test rules:** Dibutyl phosphonate  
**TSCA 8(a) PAIR:** Naphthalene  
**TSCA 8(a) CDR Exempt/Partial exemption:** Not determined  
**TSCA 8(c) calls for record of SAR:** Trimethyl phosphate  
**United States inventory (TSCA 8b):** All components are listed or exempted.  
**Clean Water Act (CWA) 307:** Benzene; Toluene; Ethylbenzene; Naphthalene  
**Clean Water Act (CWA) 311:** Benzene; Toluene; Ethylbenzene; Naphthalene

**Clean Air Act Section 602 Class I Substances** : Not listed **DEA List I Chemicals (Precursor Chemicals)** : Not listed  
**Clean Air Act Section 602 Class II Substances** : Not listed **DEA List II Chemicals (Essential Chemicals)** : Not listed  
**Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)** : Listed

**SARA 302/304****Composition/information on ingredients**

| Name            | %    | EHS  | SARA 302 TPQ |           | SARA 304 RQ |           |
|-----------------|------|------|--------------|-----------|-------------|-----------|
|                 |      |      | (lbs)        | (gallons) | (lbs)       | (gallons) |
| Sulphur Dioxide | ≤0.1 | Yes. | 500          | -         | 500         | -         |

**SARA 304 RQ** : 16947842.7 lbs / 7694320.6 kg [2377338.5 gal / 8999205.4 L]

**SARA 311/312**

**Hazard classifications** : SKIN SENSITIZATION - Category 1  
ASPIRATION HAZARD - Category 1

**Composition/information on ingredients**

| Name                                                   | Classification                  |
|--------------------------------------------------------|---------------------------------|
| Distillates (petroleum), hydrotreated light paraffinic | ASPIRATION HAZARD - Category 1  |
| Alkyl acetamide                                        | SKIN SENSITIZATION - Category 1 |
| Substituted hydrocarbyl sulfide                        | SKIN SENSITIZATION - Category 1 |
| Long chain hydroxyalkylamine                           | SKIN SENSITIZATION - Category 1 |

**SARA 313** : This product (does/not) contain toxic chemicals subject to the reporting requirements of SARA Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

| Product name    | CAS number | % |
|-----------------|------------|---|
| Not applicable. |            |   |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**State regulations**

**Massachusetts** : The following components are listed: Distillates (petroleum), hydrotreated light paraffinic; Distillates (petroleum), hydrotreated heavy paraffinic; Distillates (petroleum), hydrotreated light naphthenic

**New York** : None of the components are listed.

**New Jersey** : None of the components are listed.

**Pennsylvania** : None of the components are listed.

**California Prop. 65**

**⚠ WARNING:** This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Trimethyl phosphate, Ethylbenzene and Naphthalene, which are known to the State of California to cause cancer, and Toluene, Sulphur Dioxide and Methanol, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

| Ingredient name     | No significant risk level | Maximum acceptable dosage level |
|---------------------|---------------------------|---------------------------------|
| Toluene             | -                         | Yes.                            |
| Sulphur Dioxide     | -                         | Yes.                            |
| Methanol            | -                         | Yes.                            |
| Trimethyl phosphate | Yes.                      | -                               |
| Benzene             | Yes.                      | Yes.                            |
| Ethylbenzene        | Yes.                      | -                               |
| Naphthalene         | Yes.                      | -                               |

**Section 16. Other information**

**Revision date** : 04/02/2020 **Supersedes** : 04/15/2015

**Revised Section(s)** : 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16. **Prepared by** : KMK Regulatory Services Inc.

**Notice to reader**

THE INFORMATION CONTAINED IN THIS SDS RELATES ONLY TO THE SPECIFIC MATERIAL IDENTIFIED. IT DOES NOT COVER USE OF THAT MATERIAL IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PARTICULAR PROCESS. IN COMPLIANCE WITH 29 C.F.R. 1910.1200(g), CHS HAS PREPARED THIS SDS IN SEGMENTS, WITH THE INTENT THAT THOSE SEGMENTS BE READ TOGETHER AS A WHOLE WITHOUT TEXTUAL OMISSIONS OR ALTERATIONS. CHS BELIEVES THE INFORMATION CONTAINED HEREIN TO BE ACCURATE, BUT MAKES NO REPRESENTATION, GUARANTEE, OR WARRANTY, EXPRESS OR IMPLIED, ABOUT THE ACCURACY, RELIABILITY, OR COMPLETENESS OF THE INFORMATION OR ABOUT THE FITNESS OF CONTENTS HEREIN FOR EITHER GENERAL OR PARTICULAR PURPOSES. PERSONS REVIEWING THIS SDS SHOULD MAKE THEIR OWN DETERMINATION AS TO THE MATERIAL'S SUITABILITY AND COMPLETENESS FOR USE IN THEIR PARTICULAR APPLICATIONS.



OUR ENERGY COMES THROUGH®

A BRAND OF CHS